



**We make
highways
talk™**

- **MANAGEMENT**
- **SAFETY**
- **PRESERVATION**

International Road Dynamics Inc. develops and maintains traffic management products and systems technology that make highways talk. What are they saying? They are providing information that roadway administrators need to manage traffic, preserve infrastructure and provide safety warnings to drivers.

IRD's multi-discipline, innovative and customer-focused team is expert in advanced technologies, advanced traffic solutions and custom-designed systems.



SEPTEMBER, 2003 REV A
PRINTED IN CANADA

INTERNATIONAL ROAD DYNAMICS INC.
www.irdinc.com

TRACKER

Intersection Counter

The Tracker Intersection Counter has been designed to make intersection turning movement counts easier than ever! The counter has been configured to be comfortably held while viewing and recording traffic. The display is located at the center of the counter enabling all buttons to be accessed easily. Tracking 16 movements through an intersection could not be made easier.



Tracker & Case

FEATURES

- Simply turn on to begin count study
- Uses AA batteries
- Low power indicator
- 16 movement keys with audible feedback
- Selectable interval times
- High speed RS232 interface
- Interfaces to Road Reporter for Windows® Software

IRD products and components are protected by one or more worldwide patents and/or trademarks. IRD reserves the right to change, modify, or improve its products at any time without notice.

TRACKER

Specifications

The Tracker Intersection Counter was designed to efficiently record turning movements. For processing and reporting data, the Tracker interfaces directly to the Road Reporter software. The Tracker can be equipped with an optional input port. This port is a standard 25 Pin DB connector and can be connected to any type of contact closure, such as: a detector rack, overhead sensors or video detection. To automatically identify the direction of lane data, simply rotate the unit until indicator is pointing north. Keys have been placed equally on all sides so that rotation does not alter the users access.

TECHNICAL DATA TRACKER

Enclosure:	Aluminum (powder coat paint)
Dimensions:	17.1 cm x 17.1 cm x 3.5 cm 6.75 in x 6.75 in x 1.375 in
Display:	2 line LCD
Capacity:	10 Days
Interval Storage:	1, 5, 10, 15, and 60 minutes
Keys:	16 movements 2 programming
Ports:	Serial RS232 Power adapter Optional 25 pin input port
Power:	AA alkaline batteries
Communications:	RS232 serial communications From 300 baud to 19,200 baud



Corporate Office

702-43rd Street East
Saskatoon, Saskatchewan
Canada S7K 3T9
Tel: (306) 653-6600
Fax: (306) 242-5599
Email: info@irdinc.com

U.S. Office

2402 Spring Ridge Drive, Suite E
Spring Grove, IL
USA 60081
Tel: 1-877-444-4IRD (4473)

Publicly Traded on the TSX (Symbol IRD)
Find out more about IRD on our website: www.irdinc.com

*IRD products and components are protected by one or more worldwide patents and/or trademarks.
IRD reserves the right to change, modify, or improve its products at any time without notice.*

PRINTED IN CANADA